



319.5 MHz Wireless Receiver for M1 Security & Automation Controls

ELK-M1XRF319

Features/Benefits

- Allows an M1G and M1EZ8 controls to accept Elk's complete line of 319.5MHz wireless sensors
- Supports up to 144 individual wireless zones (sensors/points)
- Operates from the 4 wire RS-485 Data Bus
- Up to 9 M1XRF319 receivers may be connected to a single M1 or M1EZ8 control for redundancy and greater coverage

Key Specifications

- Operating Frequency: 319.5 Mhz
- Sensitivity: >105 dbm
- Operating Temperature: 0 to +120 degrees F
- Operating Voltage: 12 Volts D.C.
- Current Draw: 52mA
- Housing Dimensions: 4.13" x 7.31" x 1.5"



ELK-319KF1
Panic Button



ELK-319KF4
4 Button Keyfob



ELK-319PB1
Heavy Duty Panic



ELK-319HRR
Heat Detector



ELK-319GB
Glassbreak
Sensor



ELK-319DWM
Mini Door and
Window Sensor



ELK-319WS
Window & Shock
Sensor



ELK-319DG
All Weather
Door/Gate



ELK-319DR
Recessed
Door Contact



ELK-319PIRC
Ceiling Mount
Motion Detector



ELK-319PIRW
Wall Mount
Motion Detector



Solutions for Serious Security and Automation Professionals

(800) 797-9355 | www.elkproducts.com